

## Material Name: Hexafluoro-1,3-butadiene

\* \* \*Section 1 - IDENTIFICATION\* \* \*

#### Manufacturer Information Electronic Fluorocarbons LLC 3266 Bergey Road Hatfield PA 19440

General Information: 1-215-443-9600 Emergency #: 1-800-535-5053 Outside the US: +1-352-323-3500 (Call collect)

# Product Identifier: Hexafluoro-1,3-butadiene

## Trade Names/Synonyms

1,1,2,3,4,4,-HEXAFLUOROBUTA-1,3-DIENE; HEXAFLUOROBUTA-1,3-DIENE; HEXAFLUOROBUTADIENE-1,3; PERFLUORO-1,3-BUTADIENE; PERFLUOROBUTA-1,3-DIENE; PERFLUOROBUTADIENE-1,3; PERFLUOROBUTADIENE

## **Chemical Family**

aliphatic, halogenated hydrocarbons

#### Product Use

industrial

## **Restrictions on Use**

None known.

\* \* \*Section 2 - HAZARDS IDENTIFICATION\* \* \*

## **GHS Classification**

Flammable Gases, Category 1 Gas under pressure, Liquefied gas Acute Toxicity (Inhalation), Category 3

## **GHS LABEL ELEMENTS**

Symbol(s)



## Signal Word

DANGER

## Hazard Statement(s)

Extremely flammable gas Contains gas under pressure; may explode if heated Toxic if inhaled

## **Precautionary Statement(s)**

## Prevention

Keep away from heat, sparks, open flame, and hot surfaces - No smoking. Avoid breathing gas. Use only outdoors or in a well-ventilated area.

## Material Name: Hexafluoro-1,3-butadiene

## Response

Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Eliminate all ignition sources if safe to do so. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician.

#### Storage

Store in a well-ventilated place. Store locked up. Keep container tightly closed. Protect from sunlight. **Disposal** 

Dispose of in accordance with applications with applicable regulations.

## Other Hazards which do not Result in Classification

May cause asphyxia. May cause frostbite upon sudden release of compressed gas.

## \* \* \*Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS\* \* \*

CAS#	Component	Percent
685-63-2	HEXAFLUORO-1,3-BUTADIENE	100

# \* \* \*Section 4 - FIRST AID MEASURES\* \* \*

#### Inhalation

If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.

## Skin

If frostbite or freezing occur, immediately flush with plenty of lukewarm water (105-115 F; 41-46 C). DO NOT USE HOT WATER. If warm water is not available, gently wrap affected parts in blankets. Get immediate medical attention.

#### Eyes

Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.

#### Ingestion

If a large amount is swallowed, get medical attention.

#### **Note to Physicians**

Avoid adrenaline or other stimulants.

#### Symptoms: Immediate

frostbite, suffocation

#### Symptoms: Delayed

No information on significant adverse effects.

\* \* \*Section 5 - FIRE FIGHTING MEASURES\* \* \*

See Section 9 for Flammability Properties

#### **Specific Hazards Arising from the Chemical**

Severe fire hazard. Vapor/air mixtures are explosive. The vapor is heavier than air. Vapors or gases may ignite at distant ignition sources and flash back. Containers may rupture or explode if exposed to heat.

#### **Extinguishing Media**

alcohol-resistant foam, carbon dioxide, regular dry chemical, water

Large fires: Use regular foam or flood with fine water spray.

#### **Unsuitable Extinguishing Media**

None known.

#### **Protective Equipment and Precautions for Firefighters**

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

## Material Name: Hexafluoro-1,3-butadiene

## **Fire Fighting Measures**

Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Stay away from the ends of tanks. For fires in cargo or storage area: Cool containers with water from unmanned hose holder or monitor nozzles until well after fire is out. If this is impossible then take the following precautions: Keep unnecessary people away, isolate hazard area and deny entry. Let the fire burn. For tank, rail car or tank truck: Let burn unless leak can be stopped immediately. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. For smaller tanks or cylinders, extinguish and isolate from other flammables. Evacuation radius: 800 meters (1/2 mile). Do not attempt to extinguish fire unless flow of material can be stopped first. Flood with fine water spray. Cool containers with water. Apply water from a protected location or from a safe distance. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas.

## Hazardous Combustion Products

Combustion: carbonyl fluoride, fluorinated compounds, hydrogen fluoride, oxides of carbon

# \* \* \*Section 6 - ACCIDENTAL RELEASE MEASURES\* \* \*

## **Personal Precautions**

Wear personal protective clothing and equipment, see Section 8.

## **Environmental Precautions**

Avoid release to the environment.

## **Methods for Containment**

Keep unnecessary people away, isolate hazard area and deny entry. Ventilate closed spaces before entering.

## **Cleanup Methods**

Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Stop leak if possible without personal risk. Avoid heat, flames, sparks and other sources of ignition. Reduce vapors with water spray.

# \* \* \*Section 7 - HANDLING AND STORAGE\* \* \*

## Handling Procedures

Wash thoroughly after handling.

## **Storage Procedures**

Store and handle in accordance with all current regulations and standards. Store in a well-ventilated area. Store in a cool, dry place. Store below 52 C. Avoid heat, flames, sparks and other sources of ignition. Keep container tightly closed. Protect from sunlight. Store locked up. Subject to storage regulations: U.S. OSHA 29 CFR 1910.101. Keep separated from incompatible substances.

Incompatibilities alkali metals, combustible materials, metals, oxidizing materials

## \* \* \*Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION\* \* \*

## **Component Exposure Limits**

ACGIH, EU, OSHA, and NIOSH have not developed exposure limits for any of this product's components.

## **Component Biological Limit Values**

There are no biological limit values for any of this product's components.

## **Engineering Controls**

Ventilation equipment should be explosion-resistant if explosive concentrations of material are present. Provide local exhaust or process enclosure ventilation system. Ensure compliance with applicable exposure limits.

## PERSONAL PROTECTIVE EQUIPMENT

#### Eyes/Face

Wear splash resistant safety goggles with a faceshield. Contact lenses should not be worn. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

## Material Name: Hexafluoro-1,3-butadiene

## **Protective Clothing**

For the gas: Wear appropriate chemical resistant clothing. For the liquid: Wear appropriate protective, cold insulating clothing.

## **Glove Recommendations**

For the gas: Wear appropriate chemical resistant gloves. For the liquid: Wear insulated gloves.

## **Protective Materials**

leather, rubber

## **Respiratory Protection**

Under conditions of frequent use or heavy exposure, respiratory protection may be needed.

Respiratory protection is ranked in order from minimum to maximum.

Consider warning properties before use.

## For Unknown Concentrations or Immediately Dangerous to Life or Health -

Any supplied-air respirator with a full facepiece that is operated in a pressure-demand or other positive-pressure mode in combination with an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive-pressure mode.

Any self-contained breathing apparatus that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode.

# \* \* \*Section 9 - PHYSICAL AND CHEMICAL PROPERTIES\* \* \*

Physical State:	Gas	Appearance:	Colorless gas		
Color:	colorless	Physical Form:	compressed, liquefied gas		
Odor:	odorless	Odor Threshold:	Not available		
pH:	Not available	Melting/Freezing Point:	-132 °C		
Boiling Point:	6 - 7 °C	Flash Point:	flammable gas		
Decomposition:	Not available	Evaporation Rate:	Not available		
LEL:	7 %	UEL:	73 %		
Vapor Pressure:	25 psia @ 20 °C	Vapor Density (air = 1):	6.79 @15 °C		
Specific Gravity (water=1):	1.553 @ -20 °C	Water Solubility:	insoluble		
Log KOW:	Not available	Coeff. Water/Oil Dist:	123.03 estimated		
Auto Ignition:	Not available	Viscosity:	Not available		
Molecular Weight:	162.03	Molecular Formula:	C-F2-C-F-C-F-C-F2		

# \* \* \*Section 10 - STABILITY AND REACTIVITY\* \* \*

## **Chemical Stability**

Stable at normal temperatures and pressure.

## **Conditions to Avoid**

Avoid heat, flames, sparks and other sources of ignition. Minimize contact with material. Avoid inhalation of material or combustion by-products. Keep out of water supplies and sewers. Avoid contact with combustible materials.

## Possibility of Hazardous Reactions

Will not polymerize.

## Incompatible Materials

alkali metals, combustible materials, metals, oxidizing materials

## **Hazardous Decomposition**

Combustion: carbonyl fluoride, fluorinated compounds, hydrogen fluoride, oxides of carbon

#### Material Name: Hexafluoro-1,3-butadiene

# \* \* \*Section 11 - TOXICOLOGICAL INFORMATION\* \* \*

# Acute and Chronic Toxicity

## Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and no selected endpoints have been identified.

#### **RTECS Acute Toxicity (selected)**

The components of this material have been reviewed and RTECS publishes no data as of the date on this document.

#### **Acute Toxicity Level**

#### HEXAFLUORO-1,3-BUTADIENE (685-63-2)

Toxic: inhalation

#### **Immediate Effects**

frostbite, suffocation

#### **Delayed Effects**

No information on significant adverse effects.

#### Irritation/Corrosivity Data

No animal testing data available for skin or eyes.

#### **RTECS** Irritation

The components of this material have been reviewed and RTECS publishes no data as of the date on this document.

#### **Respiratory Sensitizer**

No data available.

#### **Dermal Sensitizer**

No data available.

#### Carcinogenicity

#### **Component Carcinogenicity**

None of this product's components are listed by ACGIH, IARC, NTP, OSHA or DFG.

#### **Mutagenic Data**

No data available.

## **RTECS Mutagenic**

The components of this material have been reviewed, and RTECS publishes data for one or more components.

#### **Reproductive Effects Data**

No data available.

#### **Tumorigenic Data**

No data available.

#### **RTECS Tumorigenic**

The components of this material have been reviewed, and RTECS publishes data for one or more components.

## Specific Target Organ Toxicity - Single Exposure

No data available.

#### Specific Target Organ Toxicity - Repeated Exposure

No data available.

#### **Aspiration Hazard**

Not applicable.

## Medical Conditions Aggravated by Exposure

heart disorders, nervous system disorders, skin disorders, respiratory disorders, kidney disorders

#### Material Name: Hexafluoro-1,3-butadiene

# \* \* \*Section 12 - ECOLOGICAL INFORMATION\* \* \*

#### **Component Analysis - Aquatic Toxicity**

No LOLI ecotoxicity data are available for this product's components.

Persistence and Degradability

No data available.

**Bioaccumulative Potential** 

No data available.

#### Mobility in Environmental Media

No data available.

## \* \* \*Section 13 - DISPOSAL CONSIDERATIONS\* \* \*

#### **Disposal Methods**

Dispose in accordance with all applicable regulations. Subject to disposal regulations: U.S. EPA 40 CFR 262. Hazardous Waste Number(s): D001.

#### **Component Waste Numbers**

The U.S. EPA has not published waste numbers for this product's components.

# \* \* \*Section 14 - TRANSPORT INFORMATION\* \* \*

## **US DOT Information**

Shipping Name: Liquefied gas, toxic, flammable, n.o.s. (Contains: HEXAFLUORO-1,3-BUTADIENE) UN/NA #: UN3160 Hazard Class: 2.3 Required Label(s): 2.3, 2.1 Additional Info.: Inhalation Hazard Zone C

#### **IMDG** Information

Shipping Name: Liquefied gas, toxic, flammable, n.o.s. (Contains: HEXAFLUORO-1,3-BUTADIENE) UN #: UN3160 Hazard Class: 2.3 Required Label(s): 2.1

## \* \* \*Section 15 - REGULATORY INFORMATION\* \* \*

## Component Analysis

#### **U.S. Federal Regulations**

None of this products components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

#### SARA 311/312 Hazardous Categories

#### Acute Health: Yes Chronic Health: No Fire: Yes Pressure: Yes Reactive: No

## **U.S. State Regulations**

None of this product's components are listed on the state lists from CA, MA, MN, NJ or PA.

Not regulated under California Proposition 65

## **Component Analysis - Inventory**

Component	CAS	US	CA	EU	AU	PH	JP	KR	CN	NZ
HEXAFLUORO-1,3-	685-63-2	Yes	NSL	EIN	No	No	Yes	Yes	Yes	No
BUTADIENE										

#### Material Name: Hexafluoro-1,3-butadiene

# \* \* \*Section 16 - OTHER INFORMATION\* \* \*

#### NFPA Ratings: Health: 3 Fire: 4 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

## Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU -Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CN - China; CPR -Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation: DSL - Domestic Substances List: EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LOLI - List Of LIsts™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR -New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; RID -European Rail Transport; RTECS - Registry of Toxic Effects of Chemical Substances®; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US -United States

#### **Other Information**

Electronic Fluorocarbons makes no express or implied warranties, guarantees or representations regarding the product or the information herein, including but not limited to any implied warranty or merchantability or fitness for use. Electronic Fluorocarbons shall not be liable for any personal injury, property or other damages of any nature, whether compensatory, consequential, exemplary, or otherwise, resulting from any publication, use or reliance upon the information herein.