

## Material Name: Difluoromethane

* * *Section 1 - IDENTIFICATION* * *		
GHS product identifier	: Difluoromethane (R32)	
Chemical name	: difluoromethane	
Other means of	: Methylene fluoride; Carbon fluoride hydride (CF2H2); Difluoromethane; Freon 32;	
identification	Genetron 32; Methylene difluoride; CH2F2; R 32	
Product use	<ul> <li>Synthetic/Analytical chemistry.</li> <li>Methylene fluoride; Carbon fluoride hydride (CF2H2); Difluoromethane; Freon</li> </ul>	
Synonym	32; Genetron 32; Methylene difluoride; CH2F2; R 32	
Supplier's details	Electronic Fluorocarbons 3266 Bergey Road	
	Hatfield PA 19440	
Emergency Telephone #	: 1-800-535-5053	
Outside the US (call collect)	1-352-323-3500	
,	* * *Section 2 - HAZARDS IDENTIFICATION* * *	
OSHA/HCS status	<ul> <li>This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).</li> </ul>	
Classification of the	: FLAMMABLE GASES - Category 1	
substance or mixture	GASES UNDER PRESSURE - Liquefied gas	
GHS label elements		
Hazard pictograms		
Signal word	: Danger	
Hazard statements	: Extremely flammable gas.	
	May form explosive mixtures with air. Contains gas under pressure; may explode if heated.	
	May cause frostbite.	
Drocautionary atotomasta	May displace oxygen and cause rapid suffocation.	
<u>Precautionary statements</u> General	: Read and follow all Safety Data Sheets (SDS'S) before use. Read label before use.	
Contral	Kead and follow all Safety Data Sheets (SDS S) before use. Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Close valve after each use and when empty. Use equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use a back flow preventative device in the piping. Use only equipment of compatible materials of construction. Always keep container in upright position. Approach suspected leak area with caution.	
Prevention	<ul> <li>Never Put cylinders into unventilated areas of passenger vehicles. Keep away from heat, sparks, open flames and hot surfaces No smoking. Use and store only outdoors or in a well ventilated place.</li> </ul>	
Response	: Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Eliminate all ignition sources if safe to do so.	

## **Material Name: Difluoromethane**

Storage	<ul> <li>Protect from sunlight. Protect from sunlight when ambient temperature exceeds 52°C/125°F. Store in a well-ventilated place.</li> </ul>
Disposal	: Not applicable.
Hazards not otherwise classified	: In addition to any other important health or physical hazards, this product may displace oxygen and cause rapid suffocation.

* * *Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS* * *		
Substance/mixture	: Substance	
Chemical name	: difluoromethane	
Other means of identification	: Methylene fluoride; Carbon fluoride hydride (CF2H2); Difluoromethane; Freon	
	32; Genetron 32; Methylene difluoride; CH2F2; R 32	

#### CAS number/other identifiers

CAS number	: 75-10-5		
Product code	: 001054		
Ingredient name		%	CAS number
Difluoromethane		100	75-10-5

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

# \* \* \*Section 4 - FIRST AID MEASURES\* \* \*

## Description of necessary first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. To avoid the risk of static discharges and gas ignition, soak contaminated clothing thoroughly with water before removing it. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: As this product is a gas, refer to the inhalation section.

## Most important symptoms/effects, acute and delayed

Potential acute health effects	<u>s</u>	
Eye contact	:	No known significant effects or critical hazards.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	No known significant effects or critical hazards.
Frostbite	:	Try to warm up the frozen tissues and seek medical attention.
Ingestion	:	As this product is a gas, refer to the inhalation section.
Over-exposure signs/symptoms		

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

# Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It
	may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

## See toxicological information (Section 11)

* * *Section 5 - FIRE FIGHTING MEASURES* * *		
Extinguishing media		
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.	
Unsuitable extinguishing media	: None known.	
Specific hazards arising from the chemical	: Contains gas under pressure. Extremely flammable gas. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion.	
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds	
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Contact supplier immediately for specialist advice. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. If involved in fire, shut off flow immediately if it can be done without risk. If this is impossible, withdraw from area and allow fire to burn. Fight fire from protected location or maximum possible distance. Eliminate all ignition sources if safe to do so.	
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.	

# \*\*\*Section 6 - ACCIDENTAL RELEASE MEASURES\*\*\*

## Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : Accidental releases pose a serious fire or explosion hazard. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing gas. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

#### Material Name: Difluoromethane

- **For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- **Environmental precautions** : Ensure emergency procedures to deal with accidental gas releases are in place to avoid contamination of the environment. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

# Methods and materials for containment and cleaning up

- Small spill
   : Immediately contact emergency personnel. Stop leak if without risk. Use spark-proof tools and explosion-proof equipment.
- Large spill
   : Immediately contact emergency personnel. Stop leak if without risk. Use spark-proof tools and explosion-proof equipment. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# \* \* \*Section 7 - HANDLING AND STORAGE\* \* \*

# Precautions for safe handling

- Protective measures
   Put on appropriate personal protective equipment (see Section 8). Contains gas under pressure. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous. Do not puncture or incinerate container. Use equipment rated for cylinder pressure. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. Use a suitable hand truck for cylinder movement.
- Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- **Conditions for safe storage, including any incompatibilities incompatibilities incompatibilities incompatibilities incompatible** materials (see Section 10). Eliminate all ignition sources. Keep container tightly closed and sealed until ready for use. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Cylinder temperatures should not exceed 52 °C (125 °F).

# \* \* \*Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION\* \* \*

## **Control parameters**

## **Occupational exposure limits**

Ingredient name	Exposure limits
Difluoromethane	AIHA WEEL (United States, 10/2011).
	TWA: 1000 ppm 8 hours.

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

## Material Name: Difluoromethane

# Safety Data Sheet

Environmental exposure	:	Emissions from ventilation or work process equipment should be checked to ensure
controls		they comply with the requirements of environmental protection legislation. In some
		cases, fume scrubbers, filters or engineering modifications to the process equipment
		will be necessary to reduce emissions to acceptable levels.

Individual protection meas	sures
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

# \* \* \* \* Section - - D\ mg]WU UbX 7 \ Ya ]WU DfcdYf]h]Yg\* \* \*

Appearance	
Physical state	: Gas. [Liquefied compressed gas.]
Color	: Colorless.
Molecular weight	: 52.03 g/mole
Molecular formula	: C-H2-F2
Boiling/condensation point	: -51.6°C (-60.9°F)
Melting/freezing point	: -136°C (-212.8°F)
Critical temperature	: 78.45°C (173.2°F)
Odor	: Odorless.
Odor threshold	: Not available.
рН	: Not available.
Flash point	: Not available.
Burning time	: Not applicable.

#### **Material Name: Difluoromethane**

Burning rate	: Not applicable.
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive	: Lower: 13%
(flammable) limits	Upper: 33%
Vapor pressure	: 205 (psig)
Vapor density	: 3.82 (air = 1)
Gas Density (lb/ft <sup>3</sup> )	: 0.959 (25°C / 77 to °F)
Relative density	Not applicable.
Solubility	: Not available.
Solubility in water	: >1.68 g/l
Partition coefficient: n-	: 0.21
octanol/water	
Auto-ignition temperature	: 530°C (986°F)
Decomposition temperature	: Not available.
SADT	: Not available.
Viscosity	: Not applicable.

* * *Section 10 - STABILITY AND REACTIVITY* * *		
Reactivity	: No specific test data related to reactivity available for this product or its ingredients.	
Chemical stability	: The product is stable.	
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.	
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow gas to accumulate in low or confined areas.	
Incompatibility with various substances	: Highly reactive or incompatible with the following materials: oxidizing materials and acids.	
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.	

Hazardous polymerization : Under normal conditions of storage and use, hazardous polymerization will not occur.

# \* \* \*Section 11 - TOXICOLOGICAL INFORMATION\* \* \*

# Information on toxicological effects

## Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Difluoromethane	LC50 Inhalation Gas. LC50 Inhalation Vapor		3780 mg/m³ 1890 g/m³	1 hours 4 hours

## Irritation/Corrosion

Not available.

Sensitization Not available. Mutagenicity Not available. Carcinogenicity Not available. **Reproductive toxicity** Not available. Teratogenicity Not available. Specific target organ toxicity (single exposure) Not available. Specific target organ toxicity (repeated exposure) Not available. Aspiration hazard Not available. Information on the likely : Not available. routes of exposure Potential acute health effects Eye contact : No known significant effects or critical hazards. Inhalation : No known significant effects or critical hazards. Skin contact : No known significant effects or critical hazards. Ingestion : As this product is a gas, refer to the inhalation section. Symptoms related to the physical, chemical and toxicological characteristics Eye contact : No specific data. : No specific data. Inhalation Skin contact : No specific data. Ingestion : No specific data. Delayed and immediate effects and also chronic effects from short and long term exposure Short term exposure Potential immediate : Not available. effects Potential delayed effects : Not available. Long term exposure : Not available. Potential immediate effects Potential delayed effects : Not available. Potential chronic health effects Not available.

## Material Name: Difluoromethane

General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

#### Numerical measures of toxicity

Acute toxicity estimates

Not available.

# \* \* \*Section 12 - ECOLOGICAL INFORMATION\* \* \*

#### Toxicity

Not available.

## Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Difluoromethane	0.21	-	low

## Mobility in soil

Soil/water partition : Not available. coefficient (Koc)

**Other adverse effects** : No known significant effects or critical hazards.

# \* \* \*Section 13 - DISPOSAL CONSIDERATIONS\* \* \*

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

	* * *Section 14 - Transport Information* * *				
	DOT	TDG	Mexico	IMDG	ΙΑΤΑ
UN number	UN3252	UN3252	UN3252	UN3252	UN3252
UN proper shipping name	DIFLUOROMETHANE OR REFRIGERANT GAS R 32	DIFLUOROMETHANE; OR REFRIGERANT GAS R 32	DIFLUOROMETHANE OR REFRIGERANT GAS R 32	DIFLUOROMETHANE (REFRIGERANT GAS R 32)	DIFLUOROMETHANE
Transport hazard class(es)	2.1	2.1	2.1	2.1	2.1
Packing group	-	-	-	-	-
Environment	No.	No.	No.	No.	No.
Additional information	Limited quantity Yes. Packaging instruction Passenger aircraft Quantity limitation: Forbidden. Cargo aircraft Quantity limitation: 150 kg Special provisions T50	Explosive Limit and Limited Quantity Index 0.125 ERAP Index 3000 Passenger Carrying Ship Index Forbidden Passenger Carrying Road or Rail Index Forbidden	-	-	Passenger and Cargo Aircraft limitation: 0 Forbidden Cargo Aircraft Only Quantity limitation: 150 kg

"Refer to CFR 49 (or authority having jurisdiction) to determine the information required for shipment of the product."

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

73/78 and the IBC Code			
to Annex II of MARPOL			
Transport in bulk according	:	Not available.	

73/78 and the IBC Code	
	* * *Section 15 - Regulatory Information* * *
U.S. Federal regulations	: TSCA 8(a) CDR Exempt/Partial exemption: Not determined United States inventory (TSCA 8b): This material is listed or exempted.
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	: Not listed
Clean Air Act Section 602 Class I Substances	: Not listed
Clean Air Act Section 602 Class II Substances	: Not listed
DEA List I Chemicals (Precursor Chemicals)	: Not listed
DEA List II Chemicals (Essential Chemicals)	: Not listed

# SARA 302/304

## Composition/information on ingredients

No products were found.

#### SARA 304 RQ

: Not applicable.

## SARA 311/312

Classification

: Fire hazard Sudden release of pressure

# Composition/information on ingredients

Name	%	Fire hazard	Sudden release of pressure		Immediate (acute) health hazard	Delayed (chronic) health hazard
Difluoromethane	100	Yes.	Yes.	No.	No.	No.

## State regulations

Massachusetts	:	This material is not listed.
New York New	:	This material is not listed.
Jersey	:	This material is not listed.
Pennsylvania	:	This material is not listed.
Canada inventory	:	This material is listed or exempted.
International regulations		
International lists	:	Australia inventory (AICS): This material is listed or exempted. China inventory (IECSC): This material is listed or exempted. Japan inventory: This material is listed or exempted. Korea inventory: This material is listed or exempted. Malaysia Inventory (EHS Register): Not determined. New Zealand Inventory of Chemicals (NZIoC): This material is listed or exempted. Philippines inventory (PICCS): This material is listed or exempted. Taiwan inventory (CSNN): Not determined.
Chemical Weapons Convention List Schedule I Chemicals	:	Not listed
Chemical Weapons Convention List Schedule II Chemicals	:	Not listed
Chemical Weapons Convention List Schedule III Chemicals	:	Not listed
Canada		
WHMIS (Canada)	:	Class A: Compressed gas.
		CEPA Toxic substances: This material is listed. Canadian ARET: This material is not listed. Canadian NPRI: This material is listed. Alberta Designated Substances: This material is not listed. Ontario Designated Substances: This material is not listed. Quebec Designated Substances: This material is not listed.

# \* \* \*Section 16 - OTHER INFORMATION\* \* \*

Canada Label requirements : Class A: Compressed gas.

#### **NFPA Ratings**

Health: 2 Fire: 4 Reactivity: 1

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

#### Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CN -China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT -Department of Transportation; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LOLI - List Of LIsts™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; RID - European Rail Transport; RTECS - Registry of Toxic Effects of Chemical Substances®; SARA - Superfund Amendments and Reauthorization Act: STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US -United States

## **Other Information**

Electronic Fluorocarbons makes no express or implied warranties, guarantees or representations regarding the product or the information herein, including but not limited to any implied warranty or merchantability or fitness for use. Electronic Fluorocarbons shall not be liable for any personal injury, property or other damages of any nature, whether compensatory, consequential, exemplary, or otherwise, resulting from any publication, use or reliance upon the information herein.