

Material Name: Methane

### \*Section 1 - IDENTIFICATION\* \* \*

**GHS** product identifier

Chemical name

: Methane : methane

Other means of

identification

Methane or natural gas; Marsh gas; Methyl hydride; CH4; Fire Damp;

Product use

: Synthetic/Analytical chemistry.

**Synonym** 

: Methane or natural gas; Marsh gas; Methyl hydride; CH4; Fire Damp;

Supplier's details

: Electronic Fluorocarbons 3266 Bergev Road Hatfield PA 19440

**Emergency telephone #** Outside the US (call collect) 1-800-535-5053 1-352-323-3500

# \* \* \*Section 2 - HAZARDS IDENTIFICATION\* \* \*

OSHA/HCS status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : FLAMMABLE GASES - Category 1

GASES UNDER PRESSURE - Compressed gas

GHS label elements

**Hazard pictograms** 





Signal word

: Danger

**Hazard statements** 

: Extremely flammable gas.

May form explosive mixtures with air.

Contains gas under pressure; may explode if heated. May displace oxygen and cause rapid suffocation.

**Precautionary statements** 

General

: Read and follow all Safety Data Sheets (SDS'S) before use. Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Close valve after each use and when empty. Use equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use a back flow preventative device in the piping. Use only equipment of compatible materials of construction. Approach suspected leak area with caution.

Prevention

: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Response

: Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Eliminate all ignition sources if safe to do so.

Storage

: Protect from sunlight when ambient temperature exceeds 52°C/125°F. Store in a wellventilated place.

**Disposal** : Not applicable.

Hazards not otherwise

classified

: In addition to any other important health or physical hazards, this product may displace oxygen and cause rapid suffocation.

Page 1 of 10

**Material Name: Methane** 

### \* \* \*Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS\* \* \*

Substance/mixture : Substance
Chemical name : methane

Other means of identification: Methane or natural gas; Marsh gas; Methyl hydride; CH4; Fire

Damp;

#### CAS number/other identifiers

**CAS number** : 74-82-8 **Product code** : 001033

Ingredient name	%	CAS number	
methane	100	74-82-8	

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

# \* \* \*Section 4 - FIRST AID MEASURES\* \* \*

# **Description of necessary first aid measures**

**Eye contact**: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention if irritation occurs.

**Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not

breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial

respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects

persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar,

tie, belt or waistband.

**Skin contact**: Wash contaminated skin with soap and water. Remove contaminated clothing and

shoes. To avoid the risk of static discharges and gas ignition, soak contaminated clothing thoroughly with water before removing it. Get medical attention if symptoms

occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.

**Ingestion**: As this product is a gas, refer to the inhalation section.

# Most important symptoms/effects, acute and delayed

### Potential acute health effects

**Eye contact**: Contact with rapidly expanding gas may cause burns or frostbite.

**Inhalation** : No known significant effects or critical hazards.

Skin contactContact with rapidly expanding gas may cause burns or frostbite.FrostbiteTry to warm up the frozen tissues and seek medical attention.

**Ingestion**: As this product is a gas, refer to the inhalation section.

### Over-exposure signs/symptoms

Eye contact: No specific data.Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments**: No specific treatment.

**Material Name: Methane** 

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. It may

be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

# \* \* \*Section 5 - FIRE FIGHTING MEASURES\* \* \*

### **Extinguishing media**

Suitable extinguishing

media

Unsuitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

: None known.

Specific hazards arising from the chemical

**Hazardous thermal** decomposition products : Contains gas under pressure. Extremely flammable gas. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Contact supplier immediately for specialist advice. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. If involved in fire, shut off flow immediately if it can be done without risk. If this is impossible, withdraw from area and allow fire to burn. Fight fire from protected location or maximum possible distance. Eliminate all ignition sources if safe to do so.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# \*\*\*Section 6 - ACCIDENTAL RELEASE MEASURES\*\*\*

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: Accidental releases pose a serious fire or explosion hazard. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing gas. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

**Environmental precautions** 

: Ensure emergency procedures to deal with accidental gas releases are in place to avoid contamination of the environment. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and materials for containment and cleaning up

Small spill

: Immediately contact emergency personnel. Stop leak if without risk. Use spark-proof tools and explosion-proof equipment.

Large spill

: Immediately contact emergency personnel. Stop leak if without risk. Use spark-proof tools and explosion-proof equipment. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

#### **Material Name: Methane**

#### \* \* \*Section 7 - HANDLING AND STORAGE\* \* \*

#### Precautions for safe handling

#### **Protective measures**

: Put on appropriate personal protective equipment (see Section 8). Contains gas under pressure. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Store and use away from heat, sparks, open flame or any other ignition source. Use explosionproof electrical (ventilating, lighting and material handling) equipment. Use only nonsparking tools. Empty containers retain product residue and can be hazardous. Do not puncture or incinerate container. Use equipment rated for cylinder pressure. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. Use a suitable hand truck for cylinder movement.

# Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# including any incompatibilities

**Conditions for safe storage**, : Store in accordance with local regulations. Store in a segregated and approved area. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Eliminate all ignition sources. Keep container tightly closed and sealed until ready for use. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Cylinder temperatures should not exceed 52 °C (125 °F).

### \* \* \*Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION\* \* \*

# **Control parameters**

### Occupational exposure limits

Ingredient name	Exposure limits		
methane	Oxygen Depletion [Asphyxiant]		

### **Appropriate** engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

### **Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

### Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with sideshields.

### Skin protection

**Material Name: Methane** 

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear antistatic protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

# \* \* \*Section 9 - Physical and Chemical Properities\* \* \*

Physical state : Gas. [Compressed gas.]

Color Colorless.

Molecular weight : 16.05 g/mole

Molecular formula : C-H4

Boiling/condensation point : -161.48°C (-258.7°F)

Melting/freezing point : -187.6°C (-305.7°F)

Critical temperature : -82.45°C (-116.4°F)

Odor : Odorless.

Odor threshold : Not available.

pH : Not available.

Flash point : Closed cup: -188.15°C (-306.7°F)

: Lower: 5%

Burning time : Not applicable.

Burning rate : Not applicable.

Evaporation rate : Not available.

Flammability (solid, gas) : Extremely flammable in the presence of the following materials or conditions: open

flames, sparks and static discharge and oxidizing materials.

Lower and upper explosive

(flammable) limitsUpper: 15%Vapor pressure: Not available.

Vapor density : 0.55 (Air = 1)Liquid Density@BP: 26.5 lb/ft3 (424.5 kg/m3)

Specific Volume (ft 3/lb) : 24.3956

Gas Density (lb/ft 3) : 0.040991 (25°C / 77 to °F)

Relative density : Not applicable.

Solubility : Not available.

Solubility in water : 0.0244 g/l

Partition coefficient: n- : 1.09

octanol/water

Auto-ignition temperature: 287°C (548.6°F)Decomposition temperature: Not available.SADT: Not available.

**Material Name: Methane** 

Viscosity : Not applicable.

# \* \* \*Section 10 - STABILITY AND REACTIVITY\* \* \*

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld,

braze, solder, drill, grind or expose containers to heat or sources of ignition.

Incompatible materials : Oxidizers

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

**Hazardous polymerization**: Under normal conditions of storage and use, hazardous polymerization will not occur.

# \* \* \*Section 11 - TOXICOLOGICAL INFORMATION\* \* \*

# Information on toxicological effects

### **Acute toxicity**

Not available.

# Irritation/Corrosion

Not available.

#### Sensitization

Not available.

### Mutagenicity

Not available.

#### Carcinogenicity

Not available.

# Reproductive toxicity

Not available.

### **Teratogenicity**

Not available.

### Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Not available.

Information on the likely routes of exposure

: Not available.

Potential acute health effects

**Material Name: Methane** 

**Eye contact** : Contact with rapidly expanding gas may cause burns or frostbite.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact**: Contact with rapidly expanding gas may cause burns or frostbite.

**Ingestion** : As this product is a gas, refer to the inhalation section.

### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.
Inhalation : No specific data.
Skin contact : No specific data.
Ingestion : No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

### Short term exposure

Potential immediate: Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

### Potential chronic health effects

Not available.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.
 Fertility effects : No known significant effects or critical hazards.

# **Numerical measures of toxicity**

### Acute toxicity estimates

Not available.

# \* \* \*Section 12 - ECOLOGICAL INFORMATION\* \* \*

# **Toxicity**

Not available.

# Persistence and degradability

Not available.

# **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
methane	1.09	-	low

# **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

Page 7 of 10

**Material Name: Methane** 

# \* \* \*Section 13 - DISPOSAL CONSIDERATIONS\* \* \*

# **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

# \* \* \*Section 14 - Transport Information\* \* \*

	DOT	TDG	Mexico	IMDG	IATA	
UN number	UN1971	UN1971	UN1971	UN1971	UN1971	
UN proper shipping name	Methane, compressed	Methane, compressed or Methane or Natural gas, compressed (with high methane content)	Methane, compressed Methane, compressed		Methane, compressed	
Transport	2.1	2.1	2.1	2.1	2.1	
hazard class(es)	TRAMMABLE ONS	<b>&amp;</b>	<u>&amp;</u>	<u>k</u>		
Packing group	-	-	-	-	-	
Environment	No.	No.	No.	No.	No.	
Additional information	-	Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.13-2.17 (Class 2).  Explosive Limit and Limited Quantity Index 0.125  ERAP Index 3000  Passenger Carrying Ship Index Forbidden  Passenger Carrying Road or Rail Index Forbidden			Passenger and Cargo AircraftQuantity limitation: 0 Forbidden Cargo Aircraft Only Quantity limitation: 150 kg	

<sup>&</sup>quot;Refer to CFR 49 (or authority having jurisdiction) to determine the information required for shipment of the product."

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according : Not available. to Annex II of MARPOL 73/78 and the IBC Code

**Material Name: Methane** 

\* \* \*Section 15 - REGULATORY INFORMATION\* \* \*

U.S. Federal regulations : TSCA 8(a) CDR Exempt/Partial exemption: Not determined

United States inventory (TSCA 8b): This material is listed or exempted.

Clean Air Act (CAA) 112 regulated flammable substances: methane:

Clean Air Act Section 112

Not listed

(b) Hazardous Air Pollutants (HAPs)

: Not listed

Clean Air Act Section 602 Class I Substances

Clean Air Act Section 602 Class II Substances : Not listed

DEA List I Chemicals

: Not listed

(Precursor Chemicals)

DEA List II Chemicals (Essential Chemicals)

: Not listed

**SARA 302/304** 

**Composition/information on ingredients** 

No products were found.

SARA 304 RQ : Not applicable.

**SARA 311/312** 

Classification : Fire hazard

Sudden release of pressure

Composition/information on ingredients

Name		Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
methane	100	Yes.	Yes.	No.	No.	No.

# State regulations

Massachusetts: This material is listed.New York New: This material is not listed.Jersey: This material is listed.Pennsylvania: This material is listed.

**International regulations** 

International lists

**National inventory** 

: This material is listed or exempted. **Australia** Canada : This material is listed or exempted. China : This material is listed or exempted. **Europe** : This material is listed or exempted. **Japan** : This material is listed or exempted. Malaysia : This material is listed or exempted. **New Zealand** : This material is listed or exempted. **Philippines** : This material is listed or exempted. Republic of Korea : This material is listed or exempted.

**Material Name: Methane** 

**Taiwan** : This material is listed or exempted.

Canada

WHMIS (Canada) : Class A: Compressed gas.

Class B-1: Flammable gas.

**CEPA Toxic substances**: This material is listed. **Canadian** 

**ARET**: This material is not listed. **Canadian NPRI**: This material is listed.

Alberta Designated Substances: This material is not listed.
Ontario Designated Substances: This material is not listed.
Quebec Designated Substances: This material is not listed.

# \* \* \*Section 16 - OTHER INFORMATION\* \* \*

Canada Label requirements : Class A: Compressed gas.

Class B-1: Flammable gas.

**NFPA Ratings** 

Health: 0 Fire: 4 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA -Comprehensive Environmental Response, Compensation, and Liability Act; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances: EPA - Environmental Protection Agency: EU - European Union: F - Fahrenheit: IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG -International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LOLI - List Of LIsts™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; RID - European Rail Transport; RTECS - Registry of Toxic Effects of Chemical Substances®; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG -Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL -Upper Explosive Limit; US - United States

#### Other Information

Electronic Fluorocarbons makes no express or implied warranties, guarantees or representations regarding the product or the information herein, including but not limited to any implied warranty or merchantability or fitness for use. Electronic Fluorocarbons shall not be liable for any personal injury, property or other damages of any nature, whether compensatory, consequential, exemplary, or otherwise, resulting from any publication, use or reliance upon the information herein.