

Material Name: Propane

Safety Data Sheet

* * *Section 1 - IDENTIFICATION* * *

GHS product identifier	:	Propane	
Chemical name	:	propane	
Other means of identification	:	Propyl hydride; n-Propane; Dimethyl methane; Bottled gas; propane in gaseous state; propane liquefied, n-Propane; Dimethylmethane; Freon 290; Liquefied petroleum gas; Lpg; Propyl hydride; R 290; C3H8; UN 1075; UN 1978; A-108; Hydrocarbon propellant.	
Product use		Synthetic/Analytical chemistry.	
Synonym	:	Propyl hydride; n-Propane; Dimethyl methane; Bottled gas; propane in gaseous state; propane liquefied, n-Propane; Dimethylmethane; Freon 290; Liquefied petroleum gas; Lpg; Propyl hydride; R 290; C3H8; UN 1075; UN 1978; A-108; Hydrocarbon propellant.	
Supplier's details	:	Electronic Fluorocarbons 3266 Bergey Road Hatfield PA 19440	
Emergency telephone # Outside the US (call collect)	:	1-800-535-5053 1-352-323-3500	
* * *Section 2 - HAZARDS IDENTIFICATION* * *			
OSHA/HCS status	:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).	
Classification of the substance or mixture	:	FLAMMABLE GASES - Category 1 GASES UNDER PRESSURE - Liquefied gas	
GHS label elements Hazard pictograms	:		
Signal word	:	Danger	
Hazard statements		Extremely flammable gas. Contains gas under pressure; may explode if heated. May cause frostbite. May form explosive mixtures in Air. May displace oxygen and cause rapid suffocation.	
Precautionary statements			
General	:	Read and follow all Safety Data Sheets (SDS'S) before use. Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Close valve after each use and when empty. Use equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use a back flow preventative device in the piping. Use only equipment of compatible materials of construction. Always keep container in upright position. Approach suspected leak area with caution.	
Prevention		Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
Response		Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Eliminate all ignition sources if safe to do so.	
Storage	:	Protect from sunlight when ambient temperature exceeds 52°C/125°F. Store in a well-ventilated place.	

Material Name: Propane

Disposal	Not applicable.
Hazards not otherwise classified	In addition to any other important health or physical hazards, this product may displace oxygen and cause rapid suffocation.

* * *Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS* * *

Substance/mixture	: Substance
Chemical name	: propane
Other means of identification	: Propyl hydride; n-Propane; Dimethyl methane; Bottled gas; propane in gaseous state;
	propane liquefied, n-Propane; Dimethylmethane; Freon 290; Liquefied petroleum gas; Lpg;
	Propylhydride; R 290; C3H8; UN 1075; UN 1978; A-108; Hydrocarbon propellant.

CAS number/other identifiers

Ingredient name	%	CAS number
Product code : 001045		
CAS number : 74-98-6		

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

* * *Section 4 - FIRST AID MEASURES* * *

Description of necessary first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	:	Wash contaminated skin with soap and water. Remove contaminated clothing and shoes. To avoid the risk of static discharges and gas ignition, soak contaminated clothing thoroughly with water before removing it. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	As this product is a gas, refer to the inhalation section.
Most important symptoms/effects, acute and delayed		
Potential acute health effect	s	
Eye contact	:	No known significant effects or critical hazards.

Inhalation	: No known significant effects or critical hazards.
Skin contac	: No known significant effects or critical hazards.
F	The forward on the forward forward and so the statistical structure for

Frostbite : Try to warm up the frozen tissues and seek medical attention.

: As this product is a gas, refer to the inhalation section. Ingestion

Over-exposure signs/symptoms

Eye contact	: No specific data.
Inhalation	: No specific data.

Skin contact : No specific data.

Material Name: Propane

Ingestion	: No specific data.
Indication of immediate med	lical attention and special treatment needed, if necessary
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

* * *Section 5 - FIRE FIGHTING MEASURES* * *		
Extinguishing media		
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.	
Unsuitable extinguishing media	: None known.	
Specific hazards arising from the chemical	: Contains gas under pressure. Extremely flammable gas. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.	
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide	
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Contact supplier immediately for specialist advice. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. If involved in fire, shut off flow immediately if it can be done without risk. If this is impossible, withdraw from area and allow fire to burn. Fight fire from protected location or maximum possible distance. Eliminate all ignition sources if safe to do so.	
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.	

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	Accidental releases pose a serious fire or explosion hazard. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing gas. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Ensure emergency procedures to deal with accidental gas releases are in place to avoid contamination of the environment. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill	:	Immediately contact emergency personnel.	Stop leak if without risk.	Use spark-proof
		tools and explosion-proof equipment.		

Material Name:	Propane
----------------	---------

Large spill

: Immediately contact emergency personnel. Stop leak if without risk. Use spark-proof tools and explosion-proof equipment. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

* * *Section 7 - HANDLING AND STORAGE* * *

Precautions for safe handling	
Protective measures	: Put on appropriate personal protective equipment (see Section 8). Contains gas under pressure. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous. Do not puncture or incinerate container. Use equipment rated for cylinder pressure. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. Use a suitable hand truck for cylinder movement.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in a segregated and approved area. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Eliminate all ignition sources. Keep container tightly closed and sealed until ready for use. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Cylinder temperatures should not exceed 52 °C (125 °F).

* * *Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION* * *

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Propane	NIOSH REL (United States, 10/2013). TWA: 1800 mg/m³ 10 hours. TWA: 1000 ppm 10 hours. OSHA PEL (United States, 2/2013). TWA: 1800 mg/m³ 8 hours. TWA: 1000 ppm 8 hours. OSHA PEL 1989 (United States, 3/1989). TWA: 1800 mg/m³ 8 hours. TWA: 1800 mg/m³ 8 hours. OSHA PEL 1989 (United States, 3/1989). TWA: 1800 mg/m³ 8 hours. TWA: 1000 ppm 8 hours.

Appropriate engineering controls	: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

	Salety Data Sheet
Material Name: Propane	
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

'*Section - - D\ mg]WU UbX'7 \ Ya]WU DfcdYf]h]Yg*

Appearance Physical state Color Molecular weight Molecular formula Boiling/condensation point	 Gas. [Liquefied compressed gas.] Colorless. 44.11 g/mole C3-H8 -161.48°C (-258.7°F)
Melting/freezing point	: -187.6°C (-305.7°F)
Critical temperature	: 96.55°C (205.8°F)
Odor	: Odorless.BUT MAY HAVE SKUNK ODOR ADDED.
Odor threshold	. Not available.
рН	: Not available.
Flash point	- Closed cup: -104°C (-155.2°F) Open cup: -104°C (-155.2°F)
Burning time	: Not applicable.
Burning rate	: Not applicable.
Evaporation rate	: Not available.
Flammability (solid, gas)	: Extremely flammable in the presence of the following materials or conditions: open flames, sparks and static discharge and oxidizing materials.
Lower and upper explosive	: Lower: 1.8%
(flammable) limits	Upper: 8.4%
Vapor pressure	: 109 (psig)
Vapor density	: 1.6 (Air = 1)

Material Name: Propane

Specific Volume (ft ³ /lb)	: 8.6206	
Gas Density (lb/ft ³)	: 0.116 (25°C / 77 to °F)	
Relative density	: Not applicable.	
Solubility	Not available.	
Solubility in water	: 0.0244 g/l	
Partition coefficient: n-	: 1.09	
octanol/water		
Auto-ignition temperature	: 287°C (548.6°F)	
Decomposition temperature	: Not available.	
SADT	: Not available.	
Viscosity	: Not applicable.	
* * *Section 10 - STABILITY AND REACTIVITY* * *		
Reactivity	: No specific test data related to reactivity available for this product or its ingredients.	
Chemical stability	: The product is stable.	
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.	
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.	
Incompatible materials	: Oxidizers	
Hazardous decomposition		
-	: Under normal conditions of storage and use, hazardous decomposition products should	
products	not be produced.	

Hazardous polymerization : Under normal conditions of storage and use, hazardous polymerization will not occur.

* * *Section 11 - TOXICOLOGICAL INFORMATION* * *

Information on toxicological effects		
Acute toxicity		
Not available.		
IDLH	: 2100 ppm	
Irritation/Corrosion		
Not available.		
Sensitization		
Not available.		
Mutagenicity		
Not available.		
Carcinogenicity		
Not available.		
Reproductive toxicity		
Not available.		
Teratogenicity		
Not available.		

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely	: Not available.
routes of exposure	

Potential acute health effects

Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: As this product is a gas, refer to the inhalation section.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure		
Potential immediate effects	: Not available.	
Potential delayed effects	: Not available.	
Long term exposure		
Potential immediate effects	: Not available.	
Potential delayed effects	: Not available.	
Potential chronic health effects		
Not available.		
General	: No known significant effects or critical hazards.	
Carcinogenicity	: No known significant effects or critical hazards.	
Mutagenicity	: No known significant effects or critical hazards.	
Teratogenicity	: No known significant effects or critical hazards.	
Developmental effects	: No known significant effects or critical hazards.	
Fertility effects	: No known significant effects or critical hazards.	

Numerical measures of toxicity

Acute toxicity estimates

Not available.

* * *Section 12 - ECOLOGICAL INFORMATION* * *

Toxicity

Not available.

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Propane	1.09	-	low

Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

Other adverse effects

: No known significant effects or critical hazards.

* * *Section 13 - DISPOSAL CONSIDERATIONS* * *

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

* * *Section 14 - Transport Information* * *					
	DOT	TDG	Mexico	IMDG	IATA
UN number	UN1978	UN1978	UN1978	UN1978	UN1978
UN proper shipping name	PROPANE	PROPANE	PROPANE	PROPANE	PROPANE
Transport hazard class(es)			2.1		
Packing group	-	-	-	-	-
Environment	No.	No.	No.	No.	No.
Additional information Limited quantity Yes. Property Packaging instruction Passenger aircraft Quantity limitation: Forbidden. Property Property Sector Passenger aircraft Quantity limitation: Forbidden. Property Property Sector Passenger aircraft Quantity limitation: Special provisions Property Property Sector Passenger aircraft Quantity limitation: Special provisions Property Property Sector Passenger aircraft Quantity limitation: Special provisions Property Proper		Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.13-2.17 (Class 2). Explosive Limit and Limited Quantity Index 0.125 ERAP Index 3000	-	-	Passenger and Cargo AircraftQuantity limitation: 0 Forbidden Cargo Aircraft Only Quantity limitation: 150 kg

Material Name: Propane

Passenger Carrying Ship Index 65	
Passenger Carrying Road or Rail Index Forbidden Special	
provisions 29, 42	

"Refer to CFR 49 (or authority having jurisdiction) to determine the information required for shipment of the product."

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according	:	Not available.
to Annex II of MARPOL		
73/78 and the IBC Code		

* * *Section 15 - REGULATORY INFORMATION* * *

U.S. Federal regulations	 TSCA 8(a) CDR Exempt/Partial exemption: Not determined United States inventory (TSCA 8b): This material is listed or exempted. Clean Air Act (CAA) 112 regulated flammable substances: propane : 		
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	Not listed		
Clean Air Act Section 602 Class I Substances	: Not listed		
Clean Air Act Section 602 Class II Substances	: Not listed		
DEA List I Chemicals (Precursor Chemicals)	: Not listed		
DEA List II Chemicals (Essential Chemicals)	: Not listed		
SARA 302/304			
Composition/information on ingredients			
No products were found.			
SARA 304 RQ <u>SARA</u>	: Not applicable.		
<u>311/312</u>			
Classification	: Fire hazard, Sudden release of pressure		

Composition/information on ingredients

Name	%	Fire hazard	Sudden release of pressure		Immediate (acute) health hazard	Delayed (chronic) health hazard
Propane	100	Yes.	Yes.	No.	No.	No.

State regulations

Massachusetts

: This material is listed.

New York

: This material is not listed.

New Jersey	: This material is listed.		
Pennsylvania	: This material is listed.		
International regulations			
International lists			
National inventory			
Australia	: This material is listed or exempted.		
Canada	: This material is listed or exempted.		
China	: This material is listed or exempted.		
Europe	: This material is listed or exempted.		
Japan	: This material is listed or exempted.		
Malaysia	: This material is listed or exempted.		
New Zealand	: This material is listed or exempted.		
Philippines	: This material is listed or exempted.		
Republic of Korea	: This material is listed or exempted.		
Taiwan	: This material is listed or exempted.		
Canada			
WHMIS (Canada)	Class A: Compressed gas. Class B-1: Flammable gas.		
	 CEPA Toxic substances: This material is not listed. Canadian ARET: This material is not listed. Canadian NPRI: This material is listed. Alberta Designated Substances: This material is not listed. Ontario Designated Substances: This material is not listed. Quebec Designated Substances: This material is not listed. 		

* * *Section 16 - OTHER INFORMATION* * *

Canada Label requirements : Class A: Compressed gas.

Class B-1: Flammable gas.

NFPA Ratings

Health: 2 Fire: 4 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe Kev / Leaend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA -Comprehensive Environmental Response, Compensation, and Liability Act; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG -International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LOLI - List Of LIsts™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; RID - European Rail Transport; RTECS - Registry of Toxic Effects of Chemical Substances®; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG -Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL -Upper Explosive Limit; US - United States

Other Information

Electronic Fluorocarbons makes no express or implied warranties, guarantees or representations regarding the product or the information herein, including but not limited to any implied warranty or merchantability or fitness for use. Electronic Fluorocarbons shall not be liable for any personal injury, property or other damages of any nature, whether compensatory, consequential, exemplary, or otherwise, resulting from any publication, use or reliance upon the information herein.